

PRODUCT DATASHEET

SUN@Home Downlight Slim 120mm

Sun@Home Downlights | Downlight with Human Centric Lighting Technology

Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



Product benefits

- Enable increased concentration and efficiency
- Improve overall activity level and daytime alertness
- Improve sleeping rhythm and -intensity
- Improve optic convenience
- Enables an improved level of clean-air-safety by killing residential germs and bad odors
- Homogenous light distribution
- Easy and quick installation

Product features

- Adjustable color temperature via Tunable White: 2,200...5,000 K
- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Innovative Fullspectrum SunLike LEDs with CRI95
- SunLike LEDs with reduced Blue Light in LED Spectrum



- Innovative luminaire coating-technology fighting household germs and odors
- Automated biorhythm feature

TECHNICAL DATA

Electrical data

Nominal wattage	8.00 W
Nominal voltage	220...240 V
Nominal current	80 mA
Mains frequency	50...60 Hz
Power factor λ	> 0.70
Operating mode	Mains voltage

Photometrical data

Light color (designation)	Tunable White
Standard deviation of color matching	< 6 sdcm
Nominal luminous flux	700 lm
Luminous flux	700 lm
Luminous efficacy	95 lm/W
Color temperature	2200...5000 K
Color rendering index Ra	> 95

Light technical data

Beam angle	110 °
Starting time	< 0.5 s

Dimensions & Weight

Product weight	107.00 g
Diameter	120.00 mm
Length	120.00 mm
Width	120.00 mm
Height	35.00 mm

Lifespan

Number of switching cycles	15000
----------------------------	-------

Lifespan	25000 h
----------	---------

Colors & materials

Product color	White
Housing color	White
Body material	Plastic
Cover material	Polystyrene (PS)

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Mounting location	Ceiling
-------------------	---------

Capabilities

Dimmable	Yes
Type of connection	Terminal
Compatible smart home technology	Google Assistant / Amazon Alexa
LED module replaceable	Not replaceable



Certificates & Standards

Standards	CE / UKCA
Protection class	II
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Complete mounting and connecting accessories included

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction SUN@HOME DOWNLIGHT SLIM
	Declarations of conformity SUN@HOME Downlight Slim

DOWNLOAD DATA



Packaging insert
SUN@HOME

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075627024	Folding box 1	127 mm x 127 mm x 58 mm	156.00 g	0.94 dm ³
4058075627031	Shipping box 6	262 mm x 134 mm x 186 mm	1071.00 g	6.53 dm ³
4058075657090	Shipping box 24	542 mm x 286 mm x 209 mm	4929.00 g	32.40 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.